



## Standard Portable Foam Fire Extinguishers

### Description

Foam Extinguishers are made of high quality ST14 by means of deep drawing.

Foam Fire Extinguishers are effective on class A & B fire.

Corrosive and impact resistant polyester paint finish (powder coating).

All Extinguishers are coated internally for optimal protection against rust and corrosion.

AFFF is an extinguishing agent which seals the burning surface against ignition.

The valve provided with safety release valve to release the excess pressure.

These extinguishers are manufactured according to international Standards and approved by local civil defence in U.A.E.

Cylinders of different capacity can be supplied upon request.

Foam Fire Extinguishers are available in cream color also.



### Specification

Model	FF6L	FF9L	FF10L	FF12L
Capacity (Ltr)	6	9	10	12
Discharge Range (M)	5	6	6	7
Discharge Time (Sec)	≥28	≥30	≥32	≥35
Test Rating	13a 113b	21a 183b	27a 183b	34a 233b
Empty Weight (Kg)	2.5	3.55	3.55	3.98
Gross Weight (Kg)	8.5	12.55	13.55	15.98
Operating Pressure (Bar)	15			
Test Pressure (Bar)	30			
Extinguishing Agent	AFFF Foam			
Temperature Range	+5°C To +60°C			
Cylinder Material	Cold Rolled Steel Sheet			
Valve	Nickle Plated With Rigid Handle & Safety Valve Pin			
Painting	Electrostatic Polyester Epoxy Resin			
Class Of Fire	A B			
Carton Size (M3)	0.014	0.024	0.024	0.03