KHIND®

Experience More

Make Safety A Reality



KHIND®
Experience More

MADE IN MALAYSIA

Emergency Light

EM 0811 NM



Specification

Voltage	220-240V~50/60Hz
Power Consumption	DC Charging (at 3W)
Lighting Source	30PCS SMD5730 (2.5W)
Type of Battery	3.2V 1800mAh LiFePO4
Recharging Time	20 hours
Operating Duration	2 Hours
Operating Ambient Temperature, ta	0°-35°C
Rated Colour Rendering Index, Ra	>70Ra
Maximum Rated Luminous Flux	250 lm
Rated Power	3W
Rated Colour Temperature	6000-7500K
Net Weight	0.4kg
Gross Weight	10.8kg (20set/ctn)
Box Dimension (LxWxH)	365 x 108 x 50mm
Carton Dimension (LxWxH)	525 x 230 x 380mm
Colour	White

Longer Operations
- up to 3 hours

IP65 Waterproof
Protection

Easy Installation

Battery Indicator

*Specifications are subject to change without prior notice.
*Pictures are for illustration purposes only.

KHIND®
Experience More

MADE IN MALAYSIA

Portable Rechargeable Lights

EM 3120 LED



Specification

Voltage	220-240V~50/60Hz
Power Consumption	3.5W (DC Charging)
LED Lamp	60pcs x 0.06W LED
Battery type	Rechargeable Lithium Ion, 3.7V 2.2Ah
Recharging Time	12 hours
Operating Duration	7 hours (Low) 4 hours (High)
Operating Ambient Temperature, ta	25°C
Rated Colour Rendering Index, Ra	>70Ra
Maximum Rated Luminous Flux	500 lm (High)
Rated Power	3.5W
Rated Colour Temperature	7,500K
Net Weight	0.97kg
Gross Weight	14.2kg (12set/ctn)
Box Dimension (LxWxH)	560 x 86 x 65
Carton Dimension (LxWxH)	365 x 215 x 580
Colour	White

Longer Operations - up to 6 hours

IP65 Waterproof Protection

Easy Installation

Battery Indicator

*Specifications are subject to change without prior notice.
*Pictures are for illustration purposes only.

KHIND®
Experience More

MADE IN MALAYSIA

Portable Rechargeable Lights

EM 2004 GT

Specification

Voltage	220-240V~50/60Hz
Power Consumption	4W (DC Charging)
LED Lamp	2T x 25pcs x 0.06W LED
Battery type	Rechargeable Lithium Ion, 3.7V 2.2Ah
Recharging Time	24 hours
Operating Duration	6 hours (Low) 3 hours (High)
Operating Ambient Temperature, ta	25°C
Rated Colour Rendering Index, Ra	>80Ra
Maximum Rated Luminous Flux	250 lm (High)
Rated Power	2W
Rated Colour Temperature	8,000-10,000K
Net Weight	0.66kg
Gross Weight	8.92kg (12set/ctn)
Box Dimension (LxWxH)	425 x 90 x 50mm
Carton Dimension (LxWxH)	482 x 105 x 100mm
Colour	White
40'HQ Loading	13,404 sets



Longer Operations - up to 6 hours

IP65 Waterproof Protection

Easy Installation

Battery Indicator

*Specifications are subject to change without prior notice.
*Pictures are for illustration purposes only.

KHIND®
Experience More

MADE IN MALAYSIA

Portable Rechargeable Lights

EM 2020 TS

Specification

Voltage	220-240V~50/60Hz
Power Consumption	2W
LED Lamp	56PCS SMD5730 4W
Battery type	Rechargeable Lithium Ion, 3.7V 2.2Ah
Recharging Time	20-24 hours
Operating Duration	6 hours (Low) 3 hours (High)
Operating Ambient Temperature, ta	25°C
Rated Colour Rendering Index, Ra	>70Ra
Maximum Rated Luminous Flux	350 lm (High)
Rated Power	2W
Rated Colour Temperature	10,000K
Net Weight	0.54kg
Gross Weight	11.8kg (20set/ctn)
Box Dimension (LxWxH)	440 x 90 x 50mm
Carton Dimension (LxWxH)	482 x 222 x 463mm
Colour	White



Longer Operations - up to 6 hours

IP65 Waterproof Protection

Easy Installation

Battery Indicator

*Specifications are subject to change without prior notice.
*Pictures are for illustration purposes only.

KHIND®
Experience More

MADE IN MALAYSIA

Portable Rechargeable Lights

EM 2007 LED

Specification

Voltage	220-240V~50/60Hz
Power Consumption	3W
LED Lamp	48pcs SMD2835 (2.88W)
Battery type	Rechargeable Lithium Ion, 3.7V 2200mAh
Recharging Time	12 hours
Operating Duration	7.5 hours (Low) 5 hours (High)
Rated Colour Rendering Index, Ra	>70Ra
Maximum Rated Luminous Flu	400 lm (High)
Rated Power	3W
Rated Colour Temperature	7500K
Net Weight	0.9kg
Gross Weight	12kg (12set/ctn)
Box Dimension (LxWxH)	388 x 86 x 65mm
Carton Dimension (LxWxH)	365 x 215 x 407mm
Colour	White
40'HQ Loading Qty	24,048 sets



Longer Operations
- up to 7.5 hours

IP65 Waterproof Protection

Easy Installation

Battery Indicator

*Specifications are subject to change without prior notice.
*Pictures are for illustration purposes only.

KHIND®
Experience More

MADE IN MALAYSIA

Portable Rechargeable Lights

EM 3030



Specification

Voltage	220-240V~50/60Hz
Power Consumption	4W
LED Lamp	36 pcs, SMD LED 2835 (3.96W)
Battery type	Rechargeable sealed lead acid, 6V 4.5Ah
Recharging Time	<20 hours
Operating Duration	6 hours (Single Head) 4 hours (Double Head)
Operating temperature	0°C~40°C
Rated Colour Rendering Index, Ra	>70Ra
Maximum Rated Luminous	600 lm (Single Head) 1100 lm (Double Head)
Rated Power	4W
Rated Colour Temperature	6000-7500K
Net Weight	1.3kg
Gross Weight	15kg (10set/ctn)
Box Dimension (LxWxH)	245 x 80 x 260mm
Carton Dimension (LxWxH)	420 x 255 x 540mm
Colour	White
40'HQ Loading Qty	11,200 sets

Longer Operations - up to 6 hours

IP65 Waterproof Protection

Easy Installation

Battery Indicator

*Specifications are subject to change without prior notice.
*Pictures are for illustration purposes only.

KHIND®
Experience More

MADE IN MALAYSIA

Portable Rechargeable Lights

EM 2030



Specification

Voltage	220-240V~50/60Hz
Power Consumption	3W
LED Lamp	SMD2835 (36x0.076W)
Battery type	Rechargeable sealed lead acid, 6V 4.5Ah
Recharging Time	20-24 hours
Operating Duration	4 hours (Double Head)
Operating temperature	25°C
Rated Colour Rendering Index, Ra	>70Ra
Maximum Rated Luminous Flux	800 lm (Double Head)
Rated Power	3W
Rated Colour Temperature	6500-7500K
Net Weight	1.5kg
Gross Weight	19.7kg (12set/ctn)
Box Dimension (LxWxH)	280 x 92 x 278mm
Carton Dimension (LxWxH)	582 x 292 x 578mm
Colour	White
40'HQ Loading Qty	8,000 sets

Longer Operations - up to 4 hours

IP65 Waterproof Protection

Easy Installation

Battery Indicator

*Specifications are subject to change without prior notice.
*Pictures are for illustration purposes only.

Exit Light KS 2023



Specification

Voltage	220-240V 50/60Hz
Power Consumption	DC Charging (at 3W)
Lighting Source	16PCS SMD2835 (0.09W)
Type of Battery	3.7V2200mAH Li-ion
Recharging Time	24hours
Operating Duration	6 hours
Operating Ambient Temperature, ta	0°-40°C
Rated Colour Rendering Index, Ra	>70Ra
Maximum Rated Luminous Flux	>30 lm
Rated Power	4W
Rated Colour Temperature	6000-7500K
Net Weight	0.7kg
Gross Weight	8kg (10set/ctn)
Box Dimension (LxWxH)	356 x 45 x 242mm
Carton Dimension (LxWxH)	370 x 240 x 500mm
Colour	White

*Specifications are subject to change without prior notice.
*Pictures are for illustration purposes only.

Longer Operations
- up to 6 hours

IP65 Waterproof Protection

Easy Installation

Battery Indicator

All in One Directions

KHIND®
Experience More

MADE IN MALAYSIA

Exit Light KS 2024



Specification

Voltage	220-240V 50/60Hz
Power Consumption	DC Charging (at 4W)
Lighting Source	642PCS SMD3030
Type of Battery	3.7V2200mAH Li-on
Recharging Time	24hours
Operating Duration	5 Hours
Operating Ambient Temperature, ta	0°-40°C
Rated Colour Rendering Index, Ra	>50Ra
Maximum Rated Luminous Flux	50 lm
Rated Power	4W
Rated Colour Temperature	6000-7500K
Net Weight	0.55kg
Gross Weight	6.5kg (10set/ctn)
Box Dimension (LxWxH)	365 x 36 x 235mm
Carton Dimension (LxWxH)	370 x 205 x 490mm
Colour	White

*Specifications are subject to change without prior notice.
*Pictures are for illustration purposes only.

Longer Operations - up to 5 hours

IP65 Waterproof Protection

Easy Installation

Battery Indicator

All in One Directions